

PCR LDPE VIVASTO
COLORED LIGHT

LOW MFI

**PRODUCT DESCRIPTION**

Regranulate is a 100% Post Consumer Recyclate (PCR)

Origin: Commercial

Source: Agricultural silage stretch and silage LDPE films

REGRANULATE COMPOSITION:

- Polymer: LDPE & LLDPE
- Color: Light Grey
- Impurities: very low gel level
- Pellet size: 3 +/- 0,1 mm

No heavy metals and other plastics content.
SVHC ad gel level analysis available on demand

OPTIONS:

- Smelles (Erema Refresher)
- Non sticky

APPLICATION:

- Technical film
- Silage film,
- Packaging,
- Refuse bags, waste bags



Stowarzyszenie
Polski Recykling



PROPERTIES	METHOD	CONDITIONS	UNIT	TOLERANCE	VALUE
MFI	ISO 1133	2,16kg, 190oC	g/10 min	+/- 0,1	0,7
MFI	ISO 1133	5,00kg, 190oC	g/10 min	+/- 0,3	2,5
DENSITY	ISO 1183	-	g/cm ³	+/- 0,075	0,97
BULK DENSITY	ISO 60:2011	-	g/dm ³	+/-5	>500
MOISTURE	SCALE OVEN	10g / 90oC/ 6min	ppm	+/-30	<300
TENSILE STRENGTH	ISO 527-1, ISO 527,2	50 mm/min Grips: 115 mm	MPa	-	>15
TENSILE MODULUS (YOUNG)	ISO 527-1, ISO 527,2	50 mm/min Grips: 115 mm	MPa	+/-25	150
ELONGATION AT BREAK	ISO 527-1, ISO 527,2	50 mm/min Grips: 115 mm	%	-	> 300
CHARPY IMPACT STRENGTH (NOTCHED A)	ISO 179	5J, 23oC	kJ/m ²	-	No Break
ASH CONTENT	ISO 3451	600oC 1h	%	-	<10%